



# ESP PERFORMANCE LUBRICANT 575

*Penetrating Adhesive Lubricant fluid to Improve Performance, Production, and Longevity in Electric Submersible Pumps.*

American Well Technology delivers a proprietary formulation and patented application process to improve performance and efficiency in electric submersible pumps, while reducing decline, failure rates, and lost production. ESP Performance Lubricant 713 is a cationic lubricant and low aromatic solvent blend that penetrates, liquifies, and mobilizes solids deposition while leaving a protective lubricating boundary film to all metal surfaces. The adhesive lubricant film reduces mechanical friction, motor torque, and fluid drag, while protective surfaces from future solids deposition.

## What It Does

- Positively Attracted to Metal Surfaces
- Penetrates and Lifts Existing Corrosion and Scale
- Fluidizes and Mobilizes Asphaltenes and Paraffins
- Applies Adhesive Lubricating Boundary Film on all Metal Surfaces
- Reduces Mechanical Friction, Motor Torque, and Fluid Drag
- Offers Extreme Protection from Corrosion, Abrasives & Solids

## Benefits

- Reduces Motor Torque and Pump Friction Due to Lubrication
- Improves Pump Efficiency and Tubular Flow
- Reduces Load & Energy Consumption
- Removes Deposited Solids from Tubulars, Perforations, and Pump Components
- Inhibits Future Solids Deposition with Adhesive Lubricant Boundary Film
- Reduces Failure Rates, Maintenance, Well Servicing, & Lost Production
- Conditions and Lubricates Elastomer Seals
- Reduces Fluid Friction, Drag, and Flowline Pressure
- Increased Production Rates
- Excellent demulsification due to reduced surface tension properties
- Reduces Damage to Surfaces and Seals from Abrasives
- Extends Mean Time Between Failures
- Non-Reactive, Compatible with or Replacement to Most Production Chemicals
- Continuous Treatment Method Range of 250-750 PPM



**Scott Rettberg**

Cell - 432-878-1197 Office 832-352-7640 [scott@americanwelltechnology.com](mailto:scott@americanwelltechnology.com)